

RESIDENTIAL Cantana Nova Cantana Nova 1050 100% polypropylene - High latex foam Væg-til-væg - Technical Details

Weight: 1050 g/m²

Material: 100% polypropylene

Structure: Tufted loop pile

Backing: High latex foam

DESCRIPTION	METHOD	DATA
-------------	--------	------

KONSTRUKTION

Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	5/32
Luvmateriale	Regulation (EU) No 1007/2011	100% polypropylene
Farvemethode	-	Forfarvet garn
Bagside	ETL	HL - High foam
Dimensioner	ISO 3018	Approx. 400/500 cm
Totalhøjde	ETL	Ca. 12,5 mm.
Slidlag	ETL	Ca. 5,0 mm.
Noppeantal	ISO 1763	Ca. 18.200 pr.m2
Totalvægt	ISO 8543	Ca. 2.950 g/m2
Luvindsatsvægt	ETL	1.050 g/m2
Luvmasse	ISO 8543.	Ca. 610 g/m2
Luvdensitet	ISO 8543.	Ca. 0,126 g/cm3

EGNETHEDSPRØVNINGER

Brugsområder	ETL	22 - Bolig - Moderat brug
Garanti mod pletter og slid	ETL	10 år
Antistatiske egenskaber	ETL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	ETL	38 dB
Isoleringsevne	ETL	Ca. 0,22 m2K/W

Lysægthed	ISO 105-B02	>5
Gnideægthed våd	ISO 105-X12	>3
Gnideægthed tør	ISO 105-X12	>3-4
Vandægthed mønstrede/melerede	ISO 105-E01	>4

SIKKERHED & MILJØ

Brandklassifikation	EN 14041	Efl
CE Mærkning	EN 14041	Certificeret
	Ydeevnedeklaration	DOPE
	Notified body no.	NA
	Ce Year	25
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK