

Technical datasheet

Product information	SPC Click	
Material	100% virgin PVC+Calcium calcite powder	
Thickness	6.3mm(4.8*0.55mm+1.5mm cork)	
Plank Size	228x1852mm	
Finish	UV Coating, Matte3-5 degree	
Emboss	EIR embossing	
Installation	Click system	
Bevel	Micro beveled	
Floor heating installation	Only suitable for underfloor water heating	
UNDERLAYMENT INFORMATION		
Item	CORK	
Overall Thickness	6.3mm (+/- 0.05, unstressed)	
REFERENCE	NORMS	RESULT
Tolerance of Length	EN 427	≤ 0.15%
Tolerance of Width	EN 427	≤ 0.15%
Tolerance on the squareness	EN 427	0.05mm
Determination of stability	EN 434	<0.15%
Thermal conductivity	EN12524	0.11W/(M.K)
Reaction to Fire	EN 13501-1	Bf1-S1
Castor Chair Resistance	EN 425	Pass
Classification	EN685	Class 33 for residential/commercial
Stain Resistance	EN423	Not affected
VOC	ISO 16000	VOC A+
Slip Resistance	DIN51130	Class R9
Residual Indentation	ISO24343-1:2007	≤ 0.1 mm
Stain Resistance	EN423	Not affected
VOC	ISO 16000	VOC A+
Residual Indentation	ISO24343-1:2007	≤0.1mm
Chemical Products Resistance	EN423	Pass
Ortho-Phthalates	US EPA 3550c:2007	None
PCP	EN 12673	None
Formaldehyde Emission	EN717-1	E1
Light fastness	EN ISO 105 B02	Blue wool scale: Stage ≥ 6